



Aire Acondicionado - Tipo Piso Techo

LONDON
Aire Acondicionado

Model name	Ceiling Floor Indoor		TUB-18HRA	TUB-24HRA	TUB-36HRSA	TUB-48HRSA	TUB-60HRSA
Power supply	V/Ph/Hz		220-240V~/50Hz/1P	220-240V~/50Hz/1P	380-415V~/50Hz/3P	380-415V~/50Hz/3P	380-415V~/50Hz/3P
Cooling	Capacity	Btu/h	18000	24000	36000	48000	60000
	Capacity	W	5300	7200	10550	14000	17000
	Input	W	1712	2230	3578	4551	6000
	Rated current	A	7,78	10,1	7,8	9,30	12,90
	EER	W/W	3,10	3,23	2,95	3,08	2,83
	Energy level		B	A	C	B	C
Heating	Capacity	Btu/h	20000	26500	40000	53000	65500
	Capacity	W	5900	7900	12000	16000	19000
	Input	W	1782	2254	3468	4432	5523
	Rated current	A	8,50	11,2	7,2	9,50	13,30
	COP	W/W	3,29	3,35	3,46	3,61	3,44
	Energy level		C	B	C	A	B
Indoor coil	Number of row		2	2	2	3	3
	Fin spacing	mm	1,5	1,5	1,5	1,5	1,5
	Fin material		Hydrophilic & Louver Fin	Hydrophilic & Louver Fin	Hydrophilic & Louver Fin	Hydrophilic & Louver Fin	Hydrophilic & Louver Fin
	Tube outside diameter	mm	φ7	φ7	φ7	φ7	φ7
	Tube material		Innergroover tube type	Innergroover tube type	Innergroover tube type	Innergroover tube type	Innergroover tube type
	Coil length x height x width	mm	795x294x25.4	795x294x25.4	940x294x25.4	1300x294x38.1	1300x294x38.1
	Number of circuit		5	6	6	10	10
Indoor fan motor	Brand		Weiling	Weiling	Weiling	Weiling	Weiling
	Model		YSK36-4P	YSK55-4R-3	YSK125-4C-1	YSK85-4B-2	YSK85-4B-2
	Input	W	102/87/77	149/125/93	158/140/124	117/101/95x2	117/101/95x2
	Running current	A	0.464/0.403/0.365	0.691/0.569/0.440	0.722/0.64/0.576	0.535/0.474/0.449x2	0.535/0.474/0.449x2
	Capacitor	uF	2,5	2,5	4,5	3,5	3,5
	Applied QTY.		1	1	1	2	2
	Speed (Hi/Me/Lo)	rpm	960/790/650	1230/1150/1045	1235/1115/960	1185/980/890	1185/980/890
Indoor air flow (Hi/Me/Lo)	m ³ /h	900/800/700	1200/1050/900	1700/1300/1100	2177/1689/1434	2177/1689/1434	
Indoor noise level (Hi/Me/Lo)	dB(A)	43/41/38	45/43/40	45/43/40	52/49/46	52/49/46	
Indoor dimension	Unit (WxHxD)	mm	1055x675x235	1055x675x235	1275x675x235	1635x675x235	1635x675x235
	Packing (WxHxD)	mm	1131x753x313	1131x753x313	1351x753x313	1711x753x313	1711x753x313
Indoor weight	Net	kg	23	24	29	38	38
	Gross	kg	29	30	35	46	46
Refrigerant	Type		R410A	R410A	R410A	R410A	R410A
Refrigerant pipe	Liquid side	mm	φ6.35	9,52	9,52	9,52	9,52
	Gas side	mm	φ12.7	φ15.88	φ19.05	φ19.05	φ19.05
Drainage water pipe diameter	mm	OD25	OD25	OD25	OD25	OD25	
Operation temperature range	°C	16 ~ 30	16 ~ 30	16 ~ 30	16 ~ 30	16 ~ 30	
Operation Control			Remote controller	Remote controller	Remote controller	Remote controller	Remote controller